



ACS-FLOW-HWR-200

Polycarboxylate superplasticizer for maximum water reduction.

Description

ACS-FLOW-HWR-200 is a high range water reducing polycarboxylate superplasticizer, designed for maximum water reduction.

Application

ACS-FLOW-HWR-200 is recommended to be used for the high binder ready-mix and precast concrete with low water/cement ratio.

- High binder ready-mix concrete.
- Precast concrete.

Advantage

- High water reduction.
- High early strength.

Dosage

0.01 - 2.0 wt .% of total binder is recommended.

However, optimal dosage shall be chosen by trial and error.

Technical specification

Item	Specs
Status	Light yellow viscous liquid
Solid content	50 ± 1.0
Specific gravity	1.08 ± 0.02 g/cm ³
pH	5.5 ± 1.0
Chloride content	Below 0.001%

Packaging

ACS-FLOW-HWR-200 is packaged depending on customer demand.

- 1100Kg IBC.
- 230 Kg Drum.

Caution

Do not allow product to freeze or be stored in temperature below freezing.

Technical support

- Professional technicians are always ready to satisfy customers needs and questions

- Please contact

TEL:+ 213(0) 541 28 28 28

TEL:+ 213(0) 541 29 29 29

ACS-CHEMICAL
KHMIS EL KHECHNA-BOUMERDES
Tel: +213(0)541 28 28 28
Tel: +213(0)541 29 29 29
E-MAIL:acs-chemical.dz

