



## ACS-FLOW-SR

Polycarboxylate superplasticizer for high slump retention.

### Description

**ACS-FLOW-SR** is a high performance polycarboxylate superplasticizer, designed for high slump retention.

### Application

**ACS-FLOW-SR** keeps slump and work-ability for an extended time.

It's recommended to be used for medium binder ready-mix concrete where high slump retention and extended workability are required.

- Medium binder ready-mix concrete.
- Self compacting concrete.
- For concrete transported over longues distances.

### Advantage

- High slump retention.
- Extended workability.
- Insensitive to temperature variation.

### Dosage

0.01 - 2.0 wt .% of total binder is recommended.

However, optimal dosage shall be chosen by trial and error.

### Technical specification

Item	Specs
Status	Viscous transparent liquid
Solid content	50 ± 1.0
Specific gravity	1.09 ± 0.02 g/cm <sup>3</sup>
pH	5.5 ± 1.0
Chloride content	Below 0.001%

### Packaging

**ACS-FLOW-SR** is packaged depending on customer demand.

- 1100Kg IBC.
- 230 Kg Drum.

### Caution

Do not allow product to freeze or be stored in temperature below freezing.

### Technical support

- Professional technicians are always ready to satisfy customers needs and questions
- Please contact

TEL:+ 213(0) 541 28 28 28

TEL:+ 213(0) 541 29 29 29

ACS-CHEMICAL  
KHMIS EL KHECHNA-BOUMERDES  
Tel: +213(0)541 28 28 28  
Tel: +213(0)541 29 29 29  
E-MAIL:acs-chemical.dz

